



DT04DV6H

CAPACITY, DIMENSIONS, WEIGHT	///
Capacity trays	4 TRAYS 600x400 - GN 1/1
Distance between trays (mm)	80
Type of rack holder	GRID
Unit size with handle WxDxH (mm)	800 x 783 x 577
Unit size without handle WxDxH (mm)	800 x 733 x 577
Chamber size WxDxH (mm)	694 x 455 x 345
Packaging	PALLET + CARTON BOX
Packaging size WxDxH (mm)	850 x 850 x 740
Unit weight (kg)	55
Unit weight with packaging (kg)	67
ELECTRICAL DATA	///
Number of engines	2
Frequency (Hz)	50
Power (kW)	7
Voltage A	400V 3N~
B	400V 2N~
C	230V ~
D	230V 3~
Current (A) A	13,5
B	16,8
C	30,3
D	23,3

Power cord/power plug	A	-
	B	-
	C	-
	D	-
WATER CONNECTION REQUIREMENTS		///
Water inlet		YES
Water drain		-
Minimum water quality standards		5° f
FUNCTIONAL CHARACTERISTICS		///
Supply		ELECTRIC
Certification		CB
Control panel		"DIGITAL WITH 6 PROGRAMS AND USB CONNECTION"
Multilingual screen		-
Cooking type		CONVECTION
Bidirectional motors		YES
Two speed regulation		YES
Max cooking temperature (°C)		260
Cooking chamber material		AISI 430
Opening door		FROM TOP TO BOTTOM
Easy clean internal glass		
STANDARD EQUIPMENT		///
Self clean system		-
Core probe		-
VARIANTS AVAIABLES		///
Certification		-
Unit size with handle WxDxH (mm)		800 x 769 x 577
Unit size without handle WxDxH (mm)		800 x 733 x 577
	Frequency (Hz)	60
	Power (kW)	-
	Voltage	A -
		B -
		C -
		D -
	Current (A)	A -
		B -
		C -
		D -
Power cord / power plug	A	-

	B	-
	C	-
	D	-
Packaging		-
Packaging size WxDxH (mm)		-
ACCESSORIES		///
Self clean system		-
Stainless steel tray rack holder		-
Stainless steel grid rack holder		"5 TRAYS GN 1/1 67mm"
Oven stand		T8
		T8S
		T8SL
Wheels kit for stand		H8
Condensation hood		-
Water condensation hood		CA8008M0
Proofer		CA8008MH
		CA8088DH
		CA8016M0
Overlapping kit for 2 ovens		SK3
Blast chiller		ASP05
		-
		-
Overlapping kit for blast chillere + 1 ovens		-
Smoker		-
Core probe		WS10
Core probe for vacuum		WS11
Water softner cover		WS12
Water softner 6800L		WPA
Water softner 12000L		-
Water pressure adaptor		-
Manual shower kit		-
"Detergent 750ML (for Self clean system or Manual shower kit)"		-
"Detergent 6KG (only with self clean system)"		-
"Detergent 10KG (only with self clean system)"		-

FEATURES

◆ Standard | ◇ Optional | - Not available

MANUAL COOKING		
Convection cooking	30°C - 285°C	◆
Mixed steam and convection cooking	90°C - 230°C	◆
Humidity		-
AUTOMATIC COOKING		
Program: possibility to memorize program	99	◆
V-EVOLUTION CONTROL WITH 6 SPEED PROGRAMS		◆
Cooking cycles for each program	n°4	◆
Automatic pre-heating setting		◆
AIR DISTRIBUTION IN THE COOKING CHAMBER		
V-BI.DIRETIONAL REVERSING FAN		◆
V-POWERFULL ENGINE		◆
Number of speed regulation	2	◆
OVERLAP SYSTEM		
V- OVERLAP CONNECTION with ovens		◇
V- OVERLAP CONNECTION with DOLCE's Proofing		◇
V- OVERLAP CONNECTION with DOLCE's Stand		◇
OTHER FUNCTIONS		
Infinity time		◆
Temperature parameter unit F° or C°		◆
V - LIGHTS	Halogen	◆
USB		◆
TECHNICAL DETAILS		
Internal glass easy clean system		◆
Thermal insulation structure (energetic efficiency)		◆
Water injection regulation	Digital	◆